Product Name: PlasterForm		Product Code: PlasterForm	
Manufacturer's Name:	American Art Clay Co., Inc. 6060 Guion Road Indianapolis, IN 46254		
Information Number: (800) 374-1600		Emergency Number: (800) 374-1600	
	Section I – Product Id	entification	
Product Name: PlasterForm Product Class: Craft		Product Size: 6.4oz.	
PlasterForm			
	Section II – Hazardous Ingredien	ts / SARA Information	
Reportable Components	CAS#	Vapor Pressure Mm Hg @ Temp	Weight Percent
Calcium Sulfate Dust Cotton Binders (unspecified)	ACIGH TLV: 10mg/cum OSH NA	A PEL 15mg/cum	92.5 0.65 6.85
Carries the AP Seal. Labe	ling conforms to ASTM D4236.		
	Section III – Physical/Chemi	cal Characteristics	
Boiling Range: NA Vapor Density: Heavier than Air. Coating V.O.C.: NA Appearance and Odor: Bandages. Cotton gauze rolls in powder.			
	Section IV – Fire and Explo	sion Hazard Data	
Flash Point: NA Flammable Limits In Air By Volume: NA – Lower Extinguishing Media: No fire hazard. Special Firefighting Procedures: No fire hazard. Unusual Fire and Explosion Hazards: No fire hazard.		Method Used: NA NA – Upper	
	Section V – Reacti	vity Data	
Stability: Stable Incompatibility (Materials to Avoid): None. Hazardous Decomposition or Byproducts: Will not occur.		Conditions to Avoid: High humidity.	

Hazardous Polymerization: Will not occur.

MATERIAL SAFETY DATA SHEET

Page 2 PlasterForm

Section VI - Health Hazard Data

Inhalation Health Risks and Symptoms of Exposure: Dust particles may cause physical irritation of nasal passage, throat & respiratory system.

Skin and Eye Contact Health Risks and Symptoms of Exposure: Eyes - rinse eyes thoroughly with water

for 15 minutes. If irritation persists, contact physician. Skin: Sufficient heat to cause burns if large mass, such as a cast of hand or an arm, is kept in contact while hardening.

Skin Absorption Health Risks and Symptoms of Exposure: Prolonged & repeated skin contact may cause irritation / dermatitis.

Ingestion Health Risks and Symptoms of Exposure: Hardening, resulting in obstruction.

Health Hazards (Acute / Chronic): See above information.

Carcinogenicity: No – NTP Carcinogens No – IARC Monographs No – OSHA regulated

Medical Conditions Generally Aggravated by Exposure: Unknown.

Emergency and First Aid Procedures: Contact your local poison control center for further health information.

Section VII – Precautions for Safe Handling and Use

Steps To Be Taken In Case Material is released or spilled: Place material into clean, dry container & cover. Vacuum up remaining dust on floor to minimize creating excessive airborne dust by sweeping. Wash spill with plenty of water.

Waste Disposal Method: Not considered as hazardous waste. Plaster of Paris may plug drains when solidified. Dispose of in accordance to Local, State or Federal regulations.

Precautions To Be Taken In Handling and Storing: Avoid contact with high humidity conditions. Water in storage to avoid premature hardening of casting material.

Other Precautions: Dew point conditions or other conditions causing the presence of water will harden plaster during storage. Product hardens in 2-15 minutes after wet application.

Section VIII - Control Measures

 Respiratory Protection: Use NIOSH approved dust respirator (nuisance dust) if concentrations exceed TLV.

 Ventilation: Recommended during casting removal.

 Protect Gloves: Impervious gloves
 Eye Protection: Safety Glasses, dust goggles.

 Other Protective Clothing or Equipment: Not needed.

 Work / Hygienic Practices: Refer to AMACO Product Encyclopedia & Safety Manual.

Page 3 PlasterForm

Section IX – Disclaimer

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Since conditions of use are beyond our control we make no warranties, expressed or implied, except those that may be contained in our written acknowledgement.

Prepared by: L. Jenkins 2007